

(19) World Intellectual Property  
Organization  
International Bureau



533966

(43) International Publication Date  
27 May 2004 (27.05.2004)




PCT

(10) International Publication Number  
**WO 2004/044995 A1**

- (51) International Patent Classification<sup>7</sup>: **H01L 33/00**,  
G02B 27/44
- (21) International Application Number:  
PCT/CH2003/000721
- (22) International Filing Date:  
4 November 2003 (04.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
02405977.6 13 November 2002 (13.11.2002) EP
- (71) Applicant (for all designated States except US): **HEP-TAGON OY** [CH/CH]; Zweigniederlassung Zürich, Badenerstrasse 569, CH-8048 Zürich (CH).
- (72) Inventors; and  
(75) Inventors/Applicants (for US only): **KETTUNEN**, Ville [FI/CH]; Saumackerstrasse 37, CH-8048 Zürich (CH). **RUDMANN**, Hartmut [DE/CH]; Löwenstrasse 21, CH-8400 Winterthur (CH). **ROSSI**, Markus [CH/CH]; Blumenaustrasse 3, CH-8645 Jona (CH).
- (74) Agent: **FREI PATENTANWALTSBÜRO AG**; Postfach 524, CH-8029 Zürich (CH).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: LIGHT EMITTING DEVICE



(57) Abstract: A light emitting device comprises an electroluminescent element (1), a housing (2) and current supply means for the electroluminescent element. It is characterized by a micro-optical element (12) being coupled to the housing (2) and being arranged in a manner that it influences light emitted by the electroluminescent element (1). The micro-optical element may be made up of micro-optical structures on a surface of an at least partially transparent layer (11) coupled to the housing (2). The micro-optical structures may for example be manufactured by directly imprinting them on the at least partially transparent layer (11) coupled to the housing or by casting an at least partially transparent layer (11) comprising the electroluminescent element to a body of the light emitting device. The diffractive optical features of the micro-optical element (12) are designed according to the position, size and shape of the one or more electroluminescent elements (1), and output light distribution of the one or more electroluminescent elements (1).



(84) **Designated States (regional):** ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*